

Ydeevnedeklaration

Nr.: 1121-CPR-JA5018

1. Identification Code	FIREGUARD S564
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Fire Stopping and Sealing Product for Linear Joint and Gap Seals, see ETA 13/1059
4. Manufacturer	Dana Lim A/S, Københavnsvej 220, DK-4600 Køge
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 1
7. Notified Body and Tasks	Exova Warringtonfire 1104
8. European Technical Assessment	Exova Warringtonfire issued European Technical Approval ETA 13/1059 on the basis of ETAG 026, edition 2011, used as European Assessment Document (EAD)
9. Declared Performance	TO ETAG 026 Edition 2011
Reaction to Fire	Class E
Resistance to Fire	Resistance to fire performance and field application in accordance with En 13501-2. See ETA 13/1059
Air Permeability	Tested according to EN1314-1 see ETA 13/1059
Dangerous Substances	See Clause 2.5
Airborne sound insulation	$R_w(C;Ctr) = 38 (-2;-9)$
Durability and serviceability	Z_1
Movement Capability	According to ISO 11600 F25LM

ETAG Clause N°	Essential Characteristics	Assessment of Characteristic	Technical Specification
Safety in case of fire			
2.4.1	Reaction to fire	Class F	EN13501-1
2.4.2	Resistance to fire	Resistance to fire performance & field of application in accordance with EN13051-2 See ETA 14/0055 clause 3.2 - Annex C	EN1366-3:2009 EN13501-2 as given in Annex C
Hygiene, Health and Environment			
2.4.3	Air Permeability	Air Permeability See clause 3.3 ETA14/0110: 600Pa	EN 1026:2000
2.4.9	Airborne Sound Insulation	See ETA 14/0110 Clause 3.9 – Rw (C;Ctr) = 38 (G;-2) dB	EN ISO 10140- 2:2010
2.4.5	Dangerous Substances	See ETA 14/0110 Clause 3.5	
Energy, Economy and heat retention			
2.4.12	Service & Durability	Z1 (0/+40c) intended for use at internal conditions with high humidity (85%) in accordance with EOTA technical documents TR024, Clause 3.12	

1. Ydeevnen for den byggevare, der er anført i punkt 1 og 2, er i overensstemmelse med den deklarerede ydeevne i punkt 9.

Denne Ydeevnedeklaration udstedes på eneansvar af den fabrikant, der er anført i punkt 4.

Underskrevet for fabrikanten og på dennes vegne:

Køge, 06.02.2015

Kenneth Holm Andersen
Kemiingenør